OXYGEN VSA SERIES

sysadvance®

VSA TECHNOLOGY

INDUSTRIAL



CARBON FOOTPRINT REDUCTION

PURE EFFICIENCY PROVEN PERFORMANCE

SYSADVANCE VSA´s deliver next-generation on-site Oxygen production through advanced Vacuum Swing Adsorption technology.

Available in skid-mounted or containerized configurations, each system combines low energy consumption, high purity, and intelligent automation for reliable, plug-and-play operation anywhere.

Engineered for maximum efficiency and minimal carbon footprint, the **SYSADVANCE** VSA range stands as the ultimate solution for industries demanding clean, continuous, and cost-effective Oxygen generation.

O_2 VSA


EN

VSA TECHNOLOGY

VSA20

- O_2 Purity: 90% | 93%
- O_2 Flow Rate: 22 Sm^3/h (0,79 TPD) | 18 Sm^3/h (0,59 TPD)
- System Efficiency: 0,53 kWh/Sm^3 | 0.63 kWh/Sm^3
- Outlet Pressure: up to 8 barg
- Total absorbed power: 11,3 kW
- Power supply: 3PH + N / 380-400V / 50Hz
- Design Code for Pressure Vessels: PED (97/23/EC)
- Design Code for Piping: DIN
- Complete package CE marked
- Standard Assembly type: SKID
- Possible alternative Assembly type: HC20ft container





VSA30

- O_2 Purity: 90% | 93%
- O_2 Flow Rate: 36 Sm^3/h (1,17 TPD) | 30 Sm^3/h (0,98 TPD)
- System Efficiency: 0,53 kWh/Sm^3 | 0.63 kWh/Sm^3
- Outlet Pressure: up to 8 barg
- Total absorbed power: 19,0 kW
- Power supply: 3PH + N / 380-400V / 50Hz
- Design Code for Pressure Vessels: PED (97/23/EC)
- Design Code for Piping: DIN
- Complete package CE marked
- Standard Assembly type: SKID
- Possible alternative Assembly type: HC20ft container

VSA60

- O_2 Purity: 90% | 93%
- O_2 Flow Rate: 72 Sm^3/h (2,34 TPD) | 60 Sm^3/h (1,95 TPD)
- System Efficiency: 0,53 kWh/Sm^3 | 0.63 kWh/Sm^3
- Outlet Pressure: up to 8 barg
- Total absorbed power: 38,0 kW
- Power supply: 3PH + N / 380-400V / 50Hz
- Design Code for Pressure Vessels: PED (97/23/EC)
- Design Code for Piping: DIN
- Complete package CE marked
- Standard Assembly type: SKID
- Possible alternative Assembly type: HC20ft container






VSA90

- O_2 Purity: 90% | 93%
- O_2 Flow Rate: 108 Sm^3/h (3,51 TPD) | 90 Sm^3/h (2,93 TPD)
- System Efficiency: 0,53 kWh/Sm^3 | 0.63 kWh/Sm^3
- Outlet Pressure: up to 8 barg
- Total absorbed power: 57,0 kW
- Power supply: 3PH + N / 380-400V / 50Hz
- Design Code for Pressure Vessels: PED (97/23/EC)
- Design Code for Piping: DIN
- Complete package CE marked
- Standard Assembly type: SKID
- Possible alternative Assembly type: HC40ft container

VSA120

- O_2 Purity: 90% | 93%
- O_2 Flow Rate: 144 Sm^3/h (4,68 TPD) | 120 Sm^3/h (3,90 TPD)
- System Efficiency: 0,53 kWh/Sm^3 | 0.63 kWh/Sm^3)
- Outlet Pressure: up to 8 barg
- Total absorbed power: 76,0 kW
- Power supply: 3PH + N / 380-400V / 50Hz
- Design Code for Pressure Vessels: PED (97/23/EC)
- Design Code for Piping: DIN
- Complete package CE marked
- Standard Assembly type: SKID
- Possible alternative Assembly type: HC40ft container



REFERENCES

PORTUGAL

- Application: Land-based Fishfarming (Turbot & Sole)
- Configuration: 2 x VSA120
- Assembly type: 2 x SKID
- O_2 Purity: 90%
- O_2 Flow Rate: 2 x 144 Sm^3/h (2 x 4,68 TPD)
- Outlet Pressure: up to 8 barg
- System Efficiency: 0,53 kWh/m^3 (0,39 kWh/kg)
- Total absorbed power: 152,0 Kw



CHILE

- Application: Land-based Fishfarming (Salmon)
- Configuration: 3 x VSA30
- Assembly type: 3 x HC20ft container
- O_2 Purity: 93%
- O_2 Flow Rate: 3 x 30 Sm^3/h (3 x 0,98 TPD)
- Outlet Pressure: up to 8 barg
- System Efficiency: 0.63 kWh/m^3 (0,47 kWh/kg)
- Total absorbed power: 57,0 kW



NICARAGUA

- Application: Gold mining (Leaching process)
- Configuration: 2 x VSA120
- Assembly type: 2 x HC40ft container
- O_2 Purity: 93%
- O_2 Flow Rate: 2 x 120 Sm^3/h (2 x 3,90 TPD)
- Outlet Pressure: up to 8 barg
- System Efficiency: 0.63 kWh/m^3 (0,47 kWh/kg)
- Total absorbed power: 152,0 kW



SPAIN

- Application: Land-based Fishfarming (Trout)
- Configuration: 2 x VSA90
- Assembly type: 2 x SKID
- O_2 Purity: 90%
- O_2 Flow Rate: 2 x 108 Sm^3/h (2 x 3,51 TPD)
- Outlet Pressure: up to 0,5 barg
- System Efficiency: 0,40 kWh/m^3 (0,295 kWh/kg)
- Total absorbed power: 114,0 kW



ITALY

- Application: Land-based Fishfarming (Trout)
- Configuration: VSA30
- Assembly type: HC20ft container
- O_2 Purity: 93%
- O_2 Flow Rate: 30 Sm^3/h (0,98 TPD)
- Outlet Pressure: up to 8 barg
- System Efficiency: 0,63 kWh/m^3 (0,47 kWh/kg)
- Total absorbed power: 19,0 kW



NEW MODELS COMMING SOON!

DIPTC_O2 VSA_V01_JAN2026_EN

SMART
OXYGEN
PRODUCTION
WITH A
GREEN
FOOTPRINT

THE
LOWEST
ENERGY
CONSUMPTION
IN ITS CLASS:
FROM
0,295KWh/Kg<

sysadvance®

sysadvance.com

© 2026 – SYSADVANCE S.A. All rights reserved.
The names, product names, business names and service marks are the property of SYSADVANCE.
We reserve the right to change the product specification without prior notice.
Images are illustrative.